

Nylon Coiled Hose

Freelin-Wade's Nylon coiled tubing is tough and abrasion resistant. The hoses are fitted with durable brass male swivel compression fittings and spring guards that are preassembled on each hose end. Bulk hoses are offered in 100 foot lengths for users wanting to assemble their own hoses.

Our Nylon Twin Hose (pictured below) has all of the same features but with the added benefit of two hoses bonded together. An intermittent bond allows for easy fitting installation and eliminates taping or tie wrapping hoses together in twin line applications. One line is yellow and the second is a natural translucent color which allows for visual flow verification. Contact Customer Service for more information.

The difference between the Self-Storing Hose and the Mini Coils is that the Self-Storing Hose includes fittings.



Features

- Economical and lightweight.
- Self retracting.
- Resists oil, grease and corrosion.
- Pre-sealed threads on swivel fittings.



Specifications

Temperature Range
-60°F to +180°F

Vacuum Rating
To 28" Hg.

Diameter Tolerances
±.004"

Working Pressure
4:1 Safety Factor

Tube Markings
FW Specifications

Resin Compliance
Meets UL94HB
Testing Requirements



Nylon Self-Storing Hose

Part Number & Color Code	OD	ID	Working Pressure		Material Length	Working Length	Retracted Length	Coil OD	MPT Fitting	Approx. Weight
			75°F/25°C	150°F/65°C						
N14-12B					12'	9'	5-1/4"		1/4"	.375 lbs.
N14-25B					25'	19'	10"		1/4"	.62 lbs.
N14-50B	.309"	1/4"	185 PSI	110 PSI	50'	37.5'	19-3/4"	3-1/2"	1/4"	.937 lbs.
N14-100					100'	75'	39-1/2"		none	1.37 lbs.
N38-12B					12'	9'	4-1/2"		3/8"	.687 lbs.
N38-25B					25'	19'	9"		3/8"	1.62 lbs.
N38-50B	.470"	3/8"	165 PSI	100 PSI	50'	37.5'	18-1/4"	5-5/8"	3/8"	1.75 lbs.
N38-100					100'	75'	36-3/4"		none	4 lbs.
N12-12B					12'	9'	4-1/4"		1/2"	.375 lbs.
N12-25B					25'	19'	8-1/2"		1/2"	.562 lbs.
N12-50B	.625"	1/2"	170 PSI	110 PSI	50'	37.5'	15-1/2"	9"	1/2"	.937 lbs.
N12-100					100'	75'	31-1/2"		none	1.37 lbs.

Variation Available:

Packaging